

BYKETOL-OK BYKETOL-SPECIAL

Leveling Additives for Solvent-Borne Systems

Composition

BYKETOL-OK	Combination of high boiling aromatics, ketones and esters
BYKETOL-SPECIAL	Combination of high boiling aromatics, ketones, esters and a polydimethylsiloxane

Typical Properties

	Density at 20°C in g/ml	Non-volatile matter in %	Flash point in °C
BYKETOL-OK	0,86 Solvents: Alkylbenzenes/Diisobutylketone/Dipentene 14/5/1	<1,0	43
BYKETOL-SPECIAL	0,87 Solvents: Alkylbenzenes/Diisobutylketone 5/1	<1,0	43

Values indicated in this data sheet describe typical properties and do not constitute specification limits.

Recommended Levels

	% additive (as supplied) based upon total formulation
BYKETOL-OK	2 - 7
BYKETOL-SPECIAL	2 - 5

Incorporation and Processing Instructions

These additives can be incorporated during any stage of the production process including post-addition.

Applications

BYKETOL-OK BYKETOL-SPECIAL	These additives are used in air drying and baking synthetic resin paints, chlorinated rubber paints, NC-modified paints and polyurethanes.
---	--

Special Features and Benefits

BYKETOL-OK BYKETOL-SPECIAL	These additives prevent surface defects, such as craters, needles, blisters, pinholes and orange peel. They also prevent boiling marks and improve leveling.
---	--