

# efka® - 3778

(formerly: EFKA-LP 3778)

**Levelling agent for coil coatings and other solvent-based and solvent-free coatings.**

---

**Composition:** Acrylic copolymer

---

**Data:**

Active ingredients	: 69 - 71%	
Solvent	: alkyl benzene with high boiling point (185-209 °C)	
Density at 20 °C	: 0.98 - 1.00 g/cm <sup>3</sup>	DIN 51757
Flashpoint	: 49 °C	ISO 3679
Colour	: max. 3	ISO 4630
Appearance	: clear to slightly hazy, colourless liquid	

---

**Addition:** 0.5 - 2.0% on total formulation

---

**Properties:** EFKA- 3778:

- improves levelling
- prevents cratering
- helps substrate wetting
- does not interfere with intercoat adhesion

---

**Application:** EFKA- 3778 is especially suitable for:

- coil coatings
  - polyurethane coatings
  - stoving enamels
  - two-pack epoxy compounds
  - air-dried alkyd systems
- 

**Incorporation:** EFKA- 3778 should be added at the end of the batch preparation.

---

**Storage:** EFKA- 3778 should be stored in a cool dry place and will keep up to one year after delivery date in original unopened container.

---

**Packaging:** 25 kg and 190 kg non-returnable containers.

---