

Efka[®] SL 3299

(old : Efka[®] 3299)



general

slip and leveling agent

Efka[®] SL 3299 is a very effective additive, which increases slip, surface smoothness and gloss. Due to its excellent compatibility properties, it is very suitable for use in high-gloss clear wood coatings. Efka[®] SL 3299 improves the orientation of matting agents in matted wood finishes and

- improves leveling and surface smoothness and gloss
- increases scratch and abrasion resistance
- prevents floating
- enhances anti-blocking characteristics
- prevents cratering

chemical nature

organically modified polysiloxane

Properties

physical form

clear liquid at 20 °C (68 °F)

shelf life

The product should be stored in a cool dry place. Haze and turbidity which can occur at temperatures below 5 °C (41 °F) have no influence on the final quality of the product and can be reversed upon heating. When kept in original unopened containers, it will keep up to 4 years.

typical properties (no supply specification)

active ingredients	~ 98%
density at 20 °C (68 °F)	~ 1.04 g/cm ³
refractive index	~ 1.440
flash point	> 100 °C (212 °F)
color	≤ 1

Application

Efka[®] SL 3299 is recommended for all kinds of solvent-based wood coatings.

recommended concentrations

0.05–0.3% on total formulation

Efka[®] SL 3299 can be added at any stage during the production process.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

[®] = registered trademark, [™] = trademark of the BASF Group, unless otherwise noted

BASF SE
Formulation Additives
67056 Ludwigshafen, Germany
www.dispersions-pigments.basf.com
formulation-additives-asia@basf.com
formulation-additives-europe@basf.com
formulation-additives-nafta@basf.com
formulation-additives-south-america@basf.com